

According to [US] OSHA (29 CFR 1910.1200) /GHS Version US V0001: April 29, 2021 / 0002 Replacing version dated / version: April 1, 2020 / 0001

SECTION I - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: Corrosion Block® Aerosol Product Code: 20012

Use of Substance/Preparation: Corrosion Block® is an industrial product designed to prevent and treat corrosion on non-ferrous and ferrous metals, protect electronic equipment, and to lubricate/penetrate mechanized parts. Uses advised against: None unless specified elsewhere

Manufacturer:	Lear Chemical Research Corp. 6182A Kestrel Road Mississauga, ON Canada L5T 1Z2
Telephone: Email:	905 564-0018 905-564-7077 (fax) info@learchem.com www.learchem.com
National Contact:	Lear Chemical Research Corp. 130 Cocoplum Drive Ste. 302 Marathon, FL 33050 1 800 256-2548
Emergency Telephone:	1 800 535-5053 (Canada & US) 1 352 323-3500 (International)

SECTION 2 – HAZARDS IDENTIFICATION

General hazard statement

Substances present at a concentration below the minimum danger threshold. Read Label and Use as Directed May cause slight eye redness (Mixture Tested < Cat2B) May cause skin dryness (Mixture Tested < Cat3) May cause laxative effect if swallowed. Do not induce vomiting. Using as directed Not Expected to be Aspiration Hazard (>24mm²/s @40°C)

Classification of the substance or mixture

OSHA/GHS classification: Signal Word: Labels:	Category 4, Flammable liquid Category 3, Aerosol WARNING None Required		
Hazard statements:		H227 – Flammable liquid	
		H229 – Pressurized container: May burst if heated	
Precautionary Statements – Prevention:		P102 – Keep away from children	
		P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition	
		SOURCES.	
		P211 – Do not spray on open flame or other ignition source	
		P280 – Wash thoroughly after handling. Manufacturer specifies No special PPE.	
Precautionary Statemen	ts – Response	P370+P378 - In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.	
Precautionary Statements – Storage:		P403+P235 – Store in a well ventilated place. Keep cool.	
		P410 + P412 – Protect from extreme sunlight conditions. Do not expose to temperatures exceeding 50°C / 122°F.	



According to [US] OSHA (29 CFR 1910.1200) /GHS Version US V0001: April 29, 2021 / 0002 Replacing version dated / version: April 1, 2020 / 0001

Precautionary Statements – Disposal: P251 – Do not pierce or burn, even after use	
	P501 – Dispose of contents/container in accordance with local, regional, national, and/or
	international regulations

Other hazards which do not result in classification None known.

Statement regarding ingredients of unknown toxicity

No data available.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous substances present: MIXTURE

Substances present at a concentration below the minimum danger threshold:

NAME:	CAS	EC	Concentration % (weight)	Special Notes
Hydrotreated neutral oil	72623-85-9	276-736-3	70-85%	<0.1% DMSO w/w extract
Stoddard solvent	8052-41-3	232-489-3	5-9%	
Tetrafluoropropene 1,3,3,3 (propellant)	29118-24-9	810-135-4	1-3%	
Carbon Dioxide (propellant)	124-38-9	204-696-9	1-3%	

SECTION 4 - FIRST AID MEASURES

 Inhalation:
 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, obtain medical attention.

 Skin Contact:
 Remove excess by wiping, followed by washing with soap and water.

 Eye Contact:
 Rinse cautiously with water for several minutes. Remove contact lenses. Continue rinsing. If eye irritation persists, get medical advice/attention.

 Ingestion:
 Unlikely route of exposure.

 Most important symptoms/effects, acute and delayed See Section 2 and Section 11.
 See Section 2 and Section 11.

 Indication of any
 immediate medical attention and special treatment needed Unlikely to be required but if necessary, treat symptomatically.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Extinguishing Media: Suitable Extinguishing Media:	CO ₂ , Dry Chemical, Foam, Water Spray
Un-Suitable Extinguishing Media:	Water Jet which might spread flames
Special Hazards arising from the s	substance or mixture:
Fire hazard:	NOT classified as a flammable aerosol
Explosion hazard:	Product is not explosive. Pressurized container: May burst if heated
Reactivity:	None to our knowledge
Advice for firefighters:	·
Firefighting instructions:	Cool containers with water spray to prevent pressure build-up, auto-ignition or explosion. Self Contained Breathing Apparatus (SCBA) may be required if containers rupture under thermal conditions.
Explosion hazard:	Aerosol containers are an explosion risk when exposed to fire.



According to [US] OSHA (29 CFR 1910.1200) /GHS Version US V0001: April 29, 2021 / 0002 Replacing version dated / version: April 1, 2020 / 0001

SECTION 6 - ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

Personal precautions, protective equipment and emergency procedures:

Eliminate sources of ignition. Stop leak if you can without risk. Keep unnecessary personnel away from spill slip hazard.

Environmental precautions: Prevent spill into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up: Collect spillage and dispose of according to Section 13. Absorb spillages onto any suitable absorbent material. Scoop absorbed substance into closing containers. Wash clothing and equipment after handling.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling

Pressurized container; Do not pierce or burn, even after use. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Store in a well ventilated place. Keep container tightly closed. Store between the following temperatures: 40 and 120 Fahrenheit and out of direct sunlight and away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of reach of children.

Specific end use(s)

Apart from the uses mentioned in section 1. No other specific uses are stipulated

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION:

CAS: 8052-41-3

Stoddard Solvent

CAS: 72623-85-9 (EC: 276-736-3)

Lubricating oils (petroleum), C20 -50, hydrotreated neutral oil-based, high-viscosity, if they contain > 3 % w/w DMSO extract

Appropriate engineering controls

Not normally required. Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Distribution, Workplace and Household Settings: No special protective equipment required

Skin protection

Distribution, Workplace and Household Settings: No special protective equipment required.

Respiratory protection

Distribution, Workplace and Household Settings: No special protective equipment required.



Corrosion Block Aerosol Safety Data Sheet According to [US] OSHA (29 CFR 1910.1200) /GHS

According to [US] OSHA (29 CFR 1910.1200) /GHS Version US V0001: April 29, 2021 / 0002 Replacing version dated / version: April 1, 2020 / 0001

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties:

I		
	Appearance: Odor:	Aerosol
	• • • • •	Characteristic
	Odor Threshold:	Not established
	pH	7
	Melting / freezing point	No data available
	Boiling point / boiling range	>100°C/212°F
	Flash Point	79.4°C /175°F PMCC
	Evaporation Rate	Slower (Butyl acetate=1)
	Flammability (solid, gas)	No data available
	Flammability Limit in Air	Solvent Component Only
	Upper flammability limit	UEL: 6.0
	Lower flammability limit	LEL: 1.0
	Vapor pressure	No data available
	Vapor density	Heavier than air (Air=1)
	Specific Gravity	0.90
	Water Solubility	Slight with agitation
	Solubility in other solvents	Soluble in Naphtha
	Partition coefficient n-octanol/water:	No data available
	Auto ignition temperature	>210°C/410°F
	Decomposition temperature	No data available
	Kinematic viscosity	25 cSt @ 40°C
	Dynamic viscosity	No data available
	VOC Content (%)	90gm/l
	Other Information	No other information available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity:	None under normal use conditions.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	None under normal use conditions.
Conditions to avoid:	Heat and extreme sunlight conditions.
Incompatible materials:	Oxidizing substances.
Hazardous decomposition products	: May release COx, NOx, SOx, H2S, smoke and irritating vapors when heated to point of decomposition. In the event of fire: see section 5.

available



According to [US] OSHA (29 CFR 1910.1200) /GHS Version US V0001: April 29, 2021 / 0002 Replacing version dated / version: April 1, 2020 / 0001

SECTION 11 - TOXICOLOGICAL INFORMATION					
CORRSION BLOCK LIQUID HAS BEEN FULLY TESTED AS A COMPLETE MIXTURE FOR ORAL, EYE AND DERMAL TOXICITY. SUPPORTING DATA BASED ON THOSE EVALUATIONS. ACUTE TOXICITY IS AT OR ABOVE CATEGORY 4.					
	0 > 5000 mg/kg 0 > 5000 mg/kg ects:	Acute Eye: Acute Vapor (estimated)	LC50 > 5000 mg/kg LC50 > 5000 ppm -Rat-Aliphatic hydrocarb LC50 > 5000 ppm -Rat-Petroleum distillate		
Germ cell mutagenicity	Skin corrosion/irritationNone found.Serious eye damage/irritationSlight eye irritation (reversible)Respiratory or skin sensitizationNone found.				
Carcinogenicity IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC. ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by					
Summary of evaluation of the CMR propertiesNo data avSTOT-single exposureInsignificarSTOT-repeated exposureInsignificar		No data available. No data available. nsignificant effects do nsignificant effects do	to 0.1% is identified as a carcinogen or potent ocumented that do not justify STOT Classificat ocumented that do not justify STOT Classificat spiration Hazard (>24mm2/s @40°C)	tion.	
Tetrafluoropropene 1,3,3,3	Acute Vapor: Acute Eye: Acute Dermal:	Possible eye bur	halation – no know significant effects ns, similar to frostbite ns, similar to frostbite		

SECTION 12- ECOLOGICAL INFORMATIONToxicityNo data available.Persistence and degradabilityPetroleum components are biodegradable in marine and soil environments.Bioaccumulative potentialNo data available.Mobility in soilNo data available.Results of PBT and vPvB assessmentPBT/vPvB assessment not available as chemical safety assessment not required/not conducted.Other adverse effectsNo data available.



According to [US] OSHA (29 CFR 1910.1200) /GHS Version US V0001: April 29, 2021 / 0002 Replacing version dated / version: April 1, 2020 / 0001

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal of the product: Disposal should be in accordance with local, state and federal regulations. Do not landfill. Waste treatment methods: Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Non-empty aerosol: Dispose of waste in an approved waste disposal facility. Do NOT landfill. Sewage disposal Treat as used oil. Other disposal recommendations Disposal should be in accordance with local, state or national legislation.

SECTION 14 - TRANSPORT INFORMATION

<u>DOT</u>	Proper Shipping Name Emergency Response Guide Number	CONSUMER COMMODITY 126
TDG	UN-No. Proper Shipping Name Hazard Class Description	UN1950 AEROSOLS 2.2 UN1950, AEROSOLS, 2.2
IATA	UN-No. Proper Shipping Name Hazard Class Description	UN1950 AEROSOLS, NON-FLAMMABLE 2.2 UN1950, AEROSOLS, NON-FLAMMABLE, 2.2
IMDG/IMO	UN-No. Proper Shipping Name Hazard Class EmS-No. Description	UN1950 AEROSOLS 2.2 F-D, S-U UN1950, AEROSOLS, 2.2
<u>RID / ADR</u>	UN-No. Proper Shipping Name Hazard Class Classification code Description	UN1950 AEROSOLS 2.2 5A UN1950 AEROSOLS, 2.2
ADN	UN-No. Proper Shipping Name Hazard Class Classification code Special Provisions Description Hazard Labels Limited Quantity Ventilation	UN1950 AEROSOLS 2.2 5A 190, 327, 344, 625 UN1950 AEROSOLS, 2.2 2.2 1 L VE04
<u>LABEL</u>		>
Transport in bul	k according to Annex II of MARPOL 7	3/78 and the IBC code: Not applicable



According to [US] OSHA (29 CFR 1910.1200) /GHS Version US V0001: April 29, 2021 / 0002 Replacing version dated / version: April 1, 2020 / 0001

SECTION 15 - REGULATORY INFORMATION

This preparation was classified in compliance with GHS Directives and is not known to be classified on any EC lists or other source literature.

WHMIS U.S. Federal Regulations: TSCA Inventory (USA) DSL (Canada) SARA 302/355 Extreme Hazard: CERCLA: SARA 313 Toxic Chemical: SARA 311/312 Hazardous: Prop 65 ELINCS (Europe) ENCS (Japan) AICS (Australia) NFPA STD.704	Not Controlled Not Regulated Reported/Include Reported /Include NO NO NO NO NO NO NO NO So to All No Yes Yes Health -1	ed Flammability-0	Reactivity-1
NFPA STD.321: HMIS	Combustible Liqu Health -1	uid, Class III 3A Flammability-0	Reactivity-1
		r iainnability-0	r tououvity=1

SECTION 16 – OTHER INFORMATION

V0002 - April 29, 2021 – Revisions Section 4, 5, 8 & 12: information updated Section 14: ORM-D Consumer commodity removed. Limited QTY Symbol added. Section 11: Toxicological Information clarified

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Lear Chemical Research Corporation be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Lear Chemical Research Corporation has been advised of the possibility of such damages.