Furling Lead Blocks

Harken recommends equipping jib reefing and asymmetric/code zero furling systems with lead blocks for safe furling from the cockpit. Lightweight, UV-stabilized Carbo blocks run exclusively on ball bearings for fast trimming under any load. Furling leads are offered separately or in complete kits.

MKIV and MKIV Ocean Jib Reefing and Furling Leads

A 57 mm Carbo ratchet maintains tension on the line so the unit furls smoothly and easily. The outboard assembly allows the line to travel outside of the stanchions, keeping the sidedecks clear. Inboard block assemblies are available for the bow pulpit, to handle two lines, for continuous line furlers, or for cutter-rigged boats with two furlers. Ball and socket bases align blocks for smooth leads aft.

Reflex Asymmetric and Code Zero Furling Leads

Two stanchion leads forward guide line outboard to keep sidedecks clear. A stanchion lead aft features a double Harken Cam-Matic for cleating continuous furling line. A Carbo T2 block with shockcord attaches aft of the double cam to keep line in place for easy access.



MKIV & MKIV OCEAN JIB REEFING & FURLING LEADS









REFLEX ASYMMETRIC & CODE ZERO FURLING LEADS

| Part | | Sheave Ø | | Weight | | Max line Ø | | Maximum working load | | |
|-------------------|---|-------------|----|--------|-----|---------------|----|-------------------------|-----|-----------------------|
| No. | Description | in | mm | oz | g | in | mm | lb | kg | Use with |
| MKIV & MKIV Ocean | | | | | | | | | | |
| 7401 | 40 mm Carbo lead block assembly | 1 9/16 | 40 | 3.7 | 106 | 3/8 | 10 | 485 | 220 | 25 mm (1") stanchions |
| 7402 | 57 mm Carbo ratchet lead block assembly | 2 1/4 | 57 | 5.4 | 152 | 3/8 | 10 | 500 | 227 | 25 mm (1") stanchions |
| 7403 | 29 mm outboard lead block assembly | 1 1/8 | 29 | 3 | 85 | 3/8 | 10 | | | 25 mm (1") stanchions |
| 7404 | Lead block kit* | | | 19.2 | 544 | 3/8 | 10 | | | 25 mm (1") stanchions |
| 7405 | 40 mm Carbo stanchion mount double lead | 1 9/16 | 40 | 5.6 | 159 | 3/8 | 10 | 485 | 220 | 25 mm (1") stanchions |
| 7407 | 57 mm Carbo lead block | 2 1/4 | 57 | 5.2 | 149 | 3/8 | 10 | 500 | 227 | 25 mm (1") stanchions |
| Reflex | | | | | | | | | | |
| 7355 | Outboard fairlead | | | 4.35 | 123 | 3/8 | 10 | | | 25 mm (1") stanchions |
| 7356 | Lead block kit** | | | 26.54 | 751 | 3/8 | 10 | | | 25 mm (1") stanchions |
| 7359 | Outboard fairlead/double cam cleat | | | 9.79 | 276 | 3/8 | 10 | | | 25 mm (1") stanchions |
| 7360 | 57 mm T2 lead block/bungee | 2 1/4 | 57 | 3.7 | 106 | 3/8 | 10 | 500 | 227 | |

*Kit includes 3 x 7403 / 1 x 7401 / 1 x 7402 / 1 cleat. **Kit includes 2 x 7355 / 1 x 7359 / 1 x 7360.



Outboard leads allow furling line to travel outboard of the stanchion to keep the sidedeck clear.