Safety Data Sheet INTERLUX ORIGINAL VARNISH

X Interiux.

Bulk Sales Reference No.: SDS Revision Date: SDS Revision Number: Sales Order: {SalesOrd} Y90 11/11/2016 E5-2

1. Identification of the preparation and company

1.1. Product identifier	
Product Identity	INTERLUX ORIGINAL VARNISH
Bulk Sales Reference No.	Y90
1.2. Relevant identified uses of the substance or mix Intended Use Application Method	tture and uses advised against See Technical Data Sheet. See Technical Data Sheet.
1.3. Details of the supplier of the safety data sheet	
Company Name	Akzo Nobel Coatings International Paint LLC 2270 Morris Avenue P. O. Box 386
Emergency	
CHEMTREC (USA)	(800) 424-9300
International Paint	(713) 527-3887
Poison Control Center	(800) 854-681
Customer Service	
International Paint	(800) 589-1267
Fax No.	(800) 631-7481
2. Hazard identi	fication of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226	Flammable liquid and vapor.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Aquatic Chronic 3;H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking. P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating	Health: 2	Flammability: 2	Reactivity: 0

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

3. Composition/information on ingredients

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Solvent naphtha (petroleum), medium aliphatic CAS Number: 0064742-88-7		Asp. Tox. 1;H304	[1]
Hydrocarbons, terpene processing by-products CAS Number: 0068956-56-9	1.0 - 10		[1]
Naphtha, petroleum, hydrotreated heavy CAS Number: 0064742-48-9	1.0 - 10	Asp. Tox. 1;H304 Flam. Liq. 3;H226	[1]
Methyl ethyl ketoxime CAS Number: 0000096-29-7	0.10 - 1.0	Carc. 2;H351 Acute Tox. 4;H312 Eye Dam. 1;H318 Skin Sens. 1;H317	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO2, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

	8. Exposure	controls and	d personal protection
	8.	1. Control p	arameters
	-	Expos	
CAS No.	Ingredient	Source	Value
0000096-29-7	Methyl ethyl ketoxime	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA,	
		CAN	
		Mexico	
		Brazil	
0064742-48-9	Naphtha, petroleum, hydrotreated heavy	OSHA	
	hydrotreated neavy	ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0064742-88-7	Solvent naphtha (petroleum),	OSHA	
	medium aliphatic	ACGIH	
		NIOSH	
		Supplier	
		OHSA,	
		CAN	
		Mexico	
		Brazil	
0068956-56-9	Hydrocarbons, terpene	OSHA	
	processing by-products	ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	

Health Data

CAS No.	Ingredient	Source	Value
0000096-29-7	Methyl ethyl ketoxime	NIOSH	
0064742-48-9	Naphtha, petroleum, hydrotreated heavy	NIOSH	
	Solvent naphtha (petroleum), medium aliphatic	NIOSH	
	Hydrocarbons, terpene processing by-products	NIOSH	

Carcinogen Data			
CAS No.	Ingredient	Source	Value
0000096-29-7	Methyl ethyl ketoxime	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-48-9		OSHA	Select Carcinogen: No
I	1		

		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-88-7 Solvent naphtha	Solvent naphtha	OSHA	Select Carcinogen: No
	alinhatic	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068956-56-9 Hydrocarbons, terpene processing by-products	OSHA	Select Carcinogen: No	
	NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties		
Appearance	Dark Coloured Liquid	
Odour threshold	Not Measured	
рН	No Established Limit	
Melting point / freezing point	Not Measured	
Initial boiling point and boiling range	149 (°C) 300 (°F)	
Flash Point	27 (°C) 80 (°F)	
Evaporation rate (Ether = 1)	Not Measured	
Flammability (solid, gas)	Not Applicable	
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1	
	Upper Explosive Limit: No Established Limit	
vapor pressure (Pa)	Not Measured	
Vapor Density	Heavier than air	
Specific Gravity	0.96	
Solubility in Water	Not Measured	
Partition coefficient n-octanol/water (Log Kow)	Not Measured	
Auto-ignition temperature	Not Measured	
Decomposition temperature	Not Measured	

Viscosity (cSt)

VOC %

No Established Limit Not Measured

Refer to the Technical Data Sheet or label where information is available.

10. Stability and reactivity

10.1. Reactivity
No data available
10.2. Chemical stability
This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
10.3. Possibility of hazardous reactions
No data available
10.4. Conditions to avoid
No data available
10.5. Incompatible materials
Strong oxidizing agents.
10.6. Hazardous decomposition products
May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

Dioxide and Carbon Monoxide.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Solvent naphtha (petroleum), medium aliphatic - (64742-88-7)	6,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	No data available
Hydrocarbons, terpene processing by-products - (68956-56-9)	No data available	No data available	No data available	No data available
Naphtha, petroleum, hydrotreated heavy - (64742-48-9)	5,000.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	No data available	No data available
Methyl ethyl ketoxime - (96-29-7)	930.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Solvent naphtha (petroleum), medium aliphatic - (64742-88-7)	800.00, Pimephales promelas	100.00, Daphnia magna	450.00 (96 hr), Selenastrum capricornutum
Hydrocarbons, terpene processing by-products - (68956-56-9)	Not Available	Not Available	0.00 (hr),
Naphtha, petroleum, hydrotreated heavy - (64742-48-9)	2,200.00, Pimephales promelas	2.60, Chaetogammarus marinus	Not Available
Methyl ethyl ketoxime - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83.00 (72 hr), Scenedesmus subspicatus

12.2. Persistence and degradability
No data available
12.3. Bioaccumulative potential
Not Measured
12.4. Mobility in soil
No data available
12.5. Results of PBT and vPvB assessment
This product contains no PBT/vPvB chemicals.
12.6. Other adverse effects
No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information				
14.1. UN number		UN 1263		
14.2. UN proper shipping na	me	PAINT		
14.3. Transport hazard class(es)				
DOT (Domestic Surface Transportation))	IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	PAINT		IMDG Proper Shipping Name	PAINT
DOT Hazard Class	3 - Flammable	e	IMDG Hazard Class Sub Class	3 - Flammable Not applicable
UN / NA Number	UN 1263			
DOT Packing Group	111		IMDG Packing Group	111
CERCLA/DOT RQ	Not Applicable Not Applicable	0	System Reference Code	181

14.4. Packing group	III			
14.5. Environmental hazards				
IMDG Marine	e Pollutant: No			
14.6. Special precautions for user				
Not Ap	pplicable			
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable				
	15. Regulatory information			
Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.			
WHMIS Classification	B2 D2B			
DOT Marine Pollutants (No Product Ingr				
DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed)				
EPCRA 311/312 Chem	EPCRA 311/312 Chemicals and RQs (>.1%) : (No Product Ingredients Listed)			
	EPCRA 302 Extremely Hazardous (>.1%) : (No Product Ingredients Listed)			
EPCRA 313 Toxic Chemicals (>.1%) : (No Product Ingredients Listed)				
Mass RTK Substances (>1%) : (No Product Ingredients Listed)				
Penn RTK Substances (>1%) : (No Product Ingredients Listed)				
Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed)				
RCRA Status: (No Product Ingredients Listed)				
N.J. RTK Substances (>1%) :				
Solvent naphtha (petroleum), medium aliphatic				
N.J. Special Hazardous Substances (>.01%):				
Diethylene triamine				
Solvent naphtha (petroleum), medium aliphatic				
N.J. Env. Hazardous Substances (>.1%) : (No Product Ingredients Listed)				
Proposition 65 - Carcinogens (>0%): (No Product Ingredients Listed)				
Proposition 65 - Female Repro Toxins (>0%): (No Product Ingredients Listed)				
	Proposition 65 - Male Repro Toxins (>0%): (No Product Ingredients Listed)			
Proposition 65 - Developmental Toxins (>0%): (No Product Ingredients Listed)				

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H351 Suspected of causing cancer.

Repeated exposure may cause skin dryness or cracking.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document