

Safety Data Sheet Starbrite Silicone Sealant 821XX

Section 1. Identification

Product Identifier Synonyms Manufacture Stock Numbers	Starbrite Silicone Sealar 821XX N/A	nt
Recommended use Uses advised against	N/A N/A	
Manufacturer Contact Address	Star brite Inc. 4041 SW 47th Avenue Fort Lauderdale, FL 3331 Contact Person: Vincent	
	Phone	Emergency

Phone	Emergency Phone	Fax
(954) 587-6280	(800) 424- 9300 Chemtrec	N/A

Section 2. Hazards Identification

Classification	ACUTE TOXICITY - ORAL - Category 4 EYE DAMAGE/IRRITATION - Category 2A SKIN CORROSION/IRRITATION - Category 2
Signal Word Pictogram	Warning
Hazard Statements	Causes serious eye irritation Causes skin irritation Harmful if swallowed
Precautionary Statements	
Response	If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical attention.

	If skin irritation occurs: Get medical advice/attention. If swallowed: Call a poison center or doctor if you feel unwell. Rinse mouth. Take off contaminated clothing and wash it before reuse.
Prevention	Do not eat, drink or smoke when using this product. Washthoroughly after handling. Wear eye protection/face protection. Wear protective gloves.
Storage	N/A
Disposal	Dispose of contents/container in accordance with all local, state and federal regulations.

Ingredients of unknown 0% toxicity

Hazards not Otherwise None known Classified

Section 3. Ingredients

CAS	Ingredient Name	Weight %
4253-34-3	Methyltriacetoxysilane	1% - 5%
17689-77-9	Ethyltriacetoxysilane	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid Measures

Eye Contact	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelids open. Obtain medical attention.
Skin Contact	No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Ingestion	If irritation or discomfort occur, obtain medical advice.
Comments	Treat according to person's condition and specifics of exposure.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media Unsuitable Extinguishing Media Auto-ignition Temperature Flammability Limits in Air Extinguishing Media

Special Fire Fighting Procedures

N/A

N/A

Not determined

Not determined

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers. Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. None known

Unusual Fire or Explosion Hazards

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Observe all personal protection equipment recommendations in Sections 5 and 8. Wipe or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.
Note	See Section 8 for information about personal protective equipment for spills.

Section 7. Handling and Storage

Handling	Use adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact.
Storage	Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

Section 8. Exposure Controls/Personal Protecction

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Linits		TWA 10ppm	TWA 10ppm	15ppm
	Ethyltriacetoxysilane	TWA 10ppm	TWA 10ppm	15ppm
Personal Protective Equipment	Goggles, Gloves			
Component Exposure Limits	Component Name: Ethyltriac Exposure Limits: See acetic Methyltriacetoxysilane CAS See acetic acid comments A water or humid air. Provide exposures within guidelines TLV: TWA 10 ppm, STEL 15	acid comment Number: 4253- cetic acid is fo adequate vent of OSHA PEL:	s Component N 34-3 Exposure rmed upon con ilation to contro	ame: Limits: tact with ol
Engineering Controls	Local Ventilation: None show Recommended	uld be needed	General Ventila	ation:
Eye Protection	Use proper protection - safe	ty glasses as a	a minimum.	
Skin Protection	Wash at mealtimes and end shoes should be removed as cleaned before reuse. Chem recommended. Suitable Glov industrial hygiene and safet	s soon as pract ical protective ves: Handle in y practices.	tical and throug gloves are accordance wit	hly h good
Respiratory Protection	No respiratory protection sh None should be needed.	ould be neede	d. Suitable Res	pirator:
Precautionary Measures	Avoid eye contact. Avoid ski	in contact. Use	reasonable ca	re.
Comment	Product evolves acetic acid w Provide ventilation during us exposure guidelines or use r temperatures above 150C (3 can form formaldehyde vapor information is readily availa When heated to temperature product can form formaldehy potential cancer hazard, a k and an irritant to the eyes, system. Safe handling condi- vapor concentrations within for formaldehyde.	se to control a respiratory pro 300F) in the pr ors. Physical ar ble on the Mat es above 150C yde vapors. Fo nown skin and nose throat, sl itions may be	cetic acid within tection. When I esence of air, p nd health hazar erial Safety Da in the presence rmaldehyde is a respiratory ser kin and digestiv maintained by I	n neated to product d ta Sheet. se of air, a nsitizer, /e keeping
Note	These precautions are for ro elevated temperatures or ac added precautions.	oom temperatu erosol/spray ap	re handling. Us oplications may	e at require

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Various
Odor	Acetic Acid Odor
Odor Threshold	N/A
Solubility	Not Determined
Partition coefficient Water/n- octanol	N/A
Viscosity	Not Determined
Specific Gravity	1.007
Density Ibs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	>212F >100C
FP Method	Closed Cup
Ph	Not Determined
Melting Point	Not Determined
Boiling Point	Not Determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not Determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	Not Determined
Vapor Pressure	Not Determined
Vapor Density	Not Determined

NoteThe above information is not intended for use in preparing product specifications.

Section 10. Stability and Reactivity

Chemical Stability Hazardous Polymerization	Stable Will not occur
Conditions to Avoid	None known
Materials to Avoid / Incompatibility	Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8.
Hazardous Decomposition Products	Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds Formaldehyde Silicon dioxide

Section 11. Toxicological Information

Special Hazard Information on	No known applicable information.
Components	

Section 12. Ecological Information

Environmental Fate and Complete information is not yet available. Distribution Environmental Effects Complete information is not yet available.

Fate and Effects in Complete information is not yet available. Waste Water Treatment Plants

Section 13. Disposal

RCRA Hazard Class (40 CFR 261)	When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO State or local laws may impose additional regulatory requirements regarding disposal.
Waste Disposal Method	We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A

Road Shipment Information (DOT) Ocean Shipment (IMDG)

Air Shipment (IATA)

Not subject to DOT regulations. Not subject to IMDG code. Not subject to IATA regulations.

Section 15. Regulatory Information

TSCA Status	The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200. All chemical substances in this material are included on or
TSOA Status	exempted from listing on the TSCA Inventory of Chemical Substances.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Titre III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 311/312 Hazard Class	Acute: No Chronic: No Fire: No Pressure: No Reactive: No
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
Note	Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known
New Jersey	Dimethyl siloxane, hydroxy-terminated (70131-67-8) Ethyltriacetoxysilane (17689-77-9) Methyltriacetoxysilane (4253- 34-3) Silica, amorphous (7631-86-9) Hydrotreated middle petroleum distillates (64742-46-7)
Pennsylvania	Dimethyl siloxane, hydroxy-terminated (70131-67-8) Silica, amorphous (7631-86-9) Hydrotreated middle petroleum distillates (64742-46-7)

Section 16. Other Information

Revision Date Disclaimer

7/22/2014

The data contained herein is based upon information that **Starbrite** believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.