





Whale Manual Bilge Pump Range

| | | | Long Life Diecast Alloy Range | | Tough and Lightweight Polypropylene Range | | | | | Compact Range | | | Portable Range | |
|----------------------------------------------------|---------------------------------------------|--------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------|---------------------------|-------------|
| 1. Select Boat Type (by length) | 0 - 6m (0 - 20 ft) | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| | 6 - 12m (20ft - 40ft) | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | Secondary bilge pump only | |
| | 12 - 24m (40ft - 80ft) | | ✓ | ✓ | ✓ | ✓ | ✓ | Secondary bilge pump only | ✓ | ✓ | Secondary bilge pump only | ✓ | | |
| 2. Appliance, Performance & Port Size | Pump Usage | Emergency Bilge Pump Out | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| | | Holding Tank Pump Out | | | | ✓ | ✓ | ✓ | ✓ | | | | | |
| | | Toilet Flush | | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | | | | |
| | | Water Ballast Pump | ✓ | ✓ | ✓ | ✓ | ✓ | | | ✓ | | | | |
| | | Approvals | Life Boats Approval • Approved by Lloyds (MCA) | | | | | Life Boats Approval • Approved by Lloyds (MCA) and USCG (Mk5 Universal MCA - Size 2) (Mk5 Double Acting - Size 3) | | | | | | |
| 3. Select Pump Model | Performance Data (at 45 strokes per minute) | | 75 ltrs (20 US gals) | 41 ltrs (11 US gals) | 67 ltrs (18 US gals) | 42 ltrs (11 US gals) | 64 ltrs (17 US gals) | 25 ltrs (7 US gals) | 37.5 ltrs (9.9 US gals) | 32 ltrs (9 US gals) | 32.75 ltrs (9 US gals) | 43.5 ltrs (11.5 US gals) | 19 ltrs (5 US gals) | |
| | Port Size | | 1 .5" (38mm) | 1 .5" (38mm) | 1 .5" (38mm) | 1.5" (38mm) | 1.5" (38mm) | 1" (25mm) | 1.5" (38mm) | 1" (25mm) | 1" (25mm) | 1.5" (38mm) | 19" (483mm) | 27" (685mm) |
| | Images (Not to Scale) | |  |  |  |  |  |  |  |  |  | | | |
| | Product Description | | Gusher 30 | Gusher 10 | Gusher Titan | Mk 5 Universal | Mk 5 Double Acting | Gusher Urchin | Compac 50 | Smartbail | Easybailer | | | |
| | Product Code | On Deck | BP3000 | BP3708 | BP4402 | BP0510 | MH5570 | BP9005 (Fixed Handle) BP9021 (Removable Handle) | / | / | / | / | | |
| | | On Bulkhead | BP3010 | BP3740 | BP4410 | | MH5550 | BP9013 | BP0350 | BP5012 | / | / | | |
| | | Thru Deck | BP3020 | | | | MH5560 | | | | / | / | | |
| | | Portable | / | / | / | / | / | / | / | / | BP1935 - Short Barrel | BP1955 - Long Barrel | | |
| | Service Kits | | | AK3051 - Service Kit for Gusher 30 | AK3706 - Service Kit for Gusher 10 (Neoprene) AK3714 - Service Kit for Gusher 10 (Nitrile) | AK9003 - Gusher Titan Service Kit (Neoprene) AK9011 - Gusher Titan Service Kit (Nitrile) | AK8050 - Service Kit for Mk 5 Universal | AK8060 - Service Kit for Mk 5 D Acting - contains: Diaphragms, Valves and Circlips AS8551 - Rocker arm assembly AS8552 - Clamping plate and nut kit | AK4400 - Service Kit for Gusher Urchin (Neoprene) AK4419 - Service Kit for Gusher Urchin (Nitrile) | AK8035 - Service Kit for Compac 50 | AK5010 - Service Kit for Smartbail | | | |
| Please note - Whale bilge pumps adhere to ISO15083 | | | | | | | | | | | | | | |



We are passionate about delivering quality, service and innovation

Marine Bilge Pumps Selection Tables



 PROUD TO MANUFACTURE IN THE UK



The Experts in Bilge Systems



From the iconic Gusher range to the original low profile Supersub Bilge pump, Whale has led the way for many decades with ground breaking pump and water system designs through to recent innovative leaps in electronically controlled systems.

This handy and simple to use guide covers our full range of Manual and Electric bilge pumps, making it easy to find the right bilge pump for you!



Whale has always put quality first, with a focus on high quality manufacturing and expertise in technology, and as a UK manufacturer, we aim to provide best in class service from our base in Bangor, Northern Ireland, and through our worldwide distribution network.

For further information:
info@whalepumps.com or www.whalepumps.com



Copyright Whale ©2018

All rights reserved. Reproduction in whole or in part without permission is prohibited. WHALE, GUSHER and GULPER are registered trademarks of Munster Simms Engineering Limited, Bangor, Northern Ireland trading as Whale. Whale's policy is one of continuous improvement and we reserve the right to change specifications without prior notice. Neither the accuracy nor completeness of the information contained in this or any product literature is guaranteed by the Company and may be subject to change at its sole discretion. Illustrations are for guidance purposes only.

Whale Electric Bilge Pump Range

| | | Low profile, Narrow Submersibles | | | | | Compact and Powerful Vertically Stacked Submersibles | | | | | | Remote Mounted | |
|---------------------------------|----------------------------------------------------------------------------|----------------------------------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 1. Select Boat Type (by length) | 0 - 6m (0 - 20 ft) | ✓ | ✓ | ✓ | | | ✓ | ✓ | | | | | ✓ | |
| | 6 - 12m (20ft - 40ft) | | | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| | 12 - 24m (40ft - 80ft) | | | | ✓ | ✓ | | | ✓ | ✓ | ✓ | ✓ | | |
| 2. Flow Rate & Design | Open Flow Rate | 500 US GPH 32 ltrs/min | 650 US GPH 40 ltrs/min | 650 US GPH 40 ltrs/min | 1050 US GPH 66 ltrs/min | 1050 US GPH 66 ltrs/min | 500 US GPH 32 ltrs/min | 950 US GPH 59 ltrs/min | 1300 US GPH 82 ltrs/min | 1300 US GPH 82 ltrs/min | 2000 US GPH 126 ltrs/min | 3000 US GPH 189 ltrs/min | 300 US GPH 19 ltrs/min | |
| | Orientation | Horizontal | Horizontal | Horizontal | Horizontal | Horizontal | Vertical | Vertical | Vertical | Vertical | Vertical | Vertical | Remote Mounted | |
| | Version Please note - Standard versions require a separate bilge switch | Standard | Standard | Automatic | Standard | Automatic | Standard | Standard | Standard | Automatic | Standard | Standard | Automatic | |
| 3. Select Pump Model | Images (Not to Scale) | |  |  |  |  |  |  |  |  |  |  |  |  |
| | Product Description | | Supersub 500 | Supersub 650 | Supersub Smart 650 | Supersub 1100 | Supersub Smart 1100 | Orca 500 | Orca 950 | Orca 1300 | Orca Auto 1300 | Orca 2000 | Orca 3000 | Bilge IC |
| | Product Code | 12 V | SS5012 | SS5022 | SS5212 | SS1012 | SS1212 | BE0500 | BE0950 | BE1450 | BE1482 | BE2002 | BE3002 | SI8284 |
| | | 24 V | / | / | / | SS1024 | SS1224 | / | / | BE1454 | BE1484 | BE2004 | BE3004 | SI8484 |
| | Outlet Size | | ¾" | ¾" & 1" stepped ports | ¾" & 1" stepped ports | 1" & 1½" stepped ports | 1" & 1½" stepped ports | ¾" | 1" & 1½" stepped ports | 1" & 1½" stepped ports | 1" & 1½" stepped ports | 1½" | 1¼" | ¾" & 1" stepped ports |
| | Accessories - Complete Your System | | BE9002 - Float Switch BE9003 - Electric Field Sensor LV1219 - Non Return Valve | BE9002 - Float Switch BE9003 - Electric Field Sensor | | BE9002 - Float Switch BE9003 - Electric Field Sensor | | BE9002 - Float Switch BE9003 - Electric Field Sensor LV1215 - Non Return Valve | BE9002 - Float Switch BE9003 - Electric Field Sensor LV1215 - Non Return Valve | BE9002 - Float Switch BE9003 - Electric Field Sensor LV1215 - Non Return Valve | LV1215 - Non Return Valve | BE9003 - Electric Field Sensor LV1215 - Non Return Valve | BE9003 - Electric Field Sensor LV1215 - Non Return Valve | |

Yellow columns indicate a pump has integrated Intelligent Control technology and is an automatic pump.
Blue columns indicate a standard model that requires a separate switch.

ref:cmcc_ps_mbilge_v2_0119